

RELED300LU2 3.5 Inch 18W Non-IC Remodel Housing

SPEC # CLT106635






BRAND

Contrast Lighting

DESCRIPTION

3.5 inch LED 18 watt non-ic remodel housing with electronic driver has .051 inch thick galvanized steel, is below ceiling accessible, takes up to .9 inch thick ceiling, and has no light leak. Housing should be at least 3 inches from insulation. 3.6 inch ceiling cut out. Max 18 watts with 2700K and 3000K or 15 watts with 4000K LED. For use with compatible trims LEDR314, LEDR315, LEDR345, LEDR347, LEDS314, LEDS315, LEDS345. 13.75 inches long x 4.6 inches wide x 5.6 inches high. Suitable for damp location. UL listed.



TRIM COLOR

BODY FINISH
Galvanized Steel
WATTAGE
DIMMER
DIMMER
DIMENSIONS
13.75"L x 4.6"W x 5.6"H


INTEGRATED LED MODULE


LAMP 1 x LED/18W/120V LED

Technical Information

LAMP COLOR 3000K
FUNCTION Downlight
CEILING TYPE Drywall with Trim
HOUSING TYPE Remodel NON IC
APERTURE SHAPE Round

SPEC # CLT106635





COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE