

IL116G Inground Uplight with Rock Guard 7W

SPEC # HAD119530



BRAND

Hadco by Signify

DESCRIPTION

IL116G 7 Watt Warm White 2700K Narrow Flood LED Inground Uplight with Rock Guard housing is fabricated from a single piece of compression molded fiberglass reinforced polyester composite pressure tested to ensure water will not wick or leak through. Bronze finish trim ring and rock guard is a textured composite material. Natural Brass trim ring and rock guard is a metal finish. Clear convex, tempered sodalime glass for high impact resistance. 2200 pound live-load rated, standard walk-over lens. 7 watt lamp with 24 or 36 degree beam spread included. 30,000 hour lamp life. Lamps have 15 degree articulation either side of vertical and 358 degree rotation without interruption of beam pattern. Pre-wired with 3 foot pigtail of 18-2 AWG wire. Includes low voltage quick connector LVC3 for easy hook up to the low voltage supply cable not included. 6.6 inch diameter x 8.4 inch height. ETL listed for wet locations. Required remote transformer, optional mounting and optical accessories sold separately.


SHADE COLOR	Clear
BODY FINISH	Bronze
WATTAGE	7W
DIMMER	Dimmable
DIMENSIONS	6.6"W x 8.4"H
INTEGRATED LED MODULE	
IAMP	1 x MR16/GU5 3 (bipin)/7W/12V LED


Technical Information

LAMP COLOR 2700K
BEAM ANGLE 36°

SPEC # HAD119530







COMPANY PROJECT FIXTURE TYPE APPROVED BY DATE