



BRAND

Hadco by Signify

DESCRIPTION

IL116 7 Watt 24 or 36 Degree Narrow Flood LED
Inground Uplight housing is fabricated from a single piece of compression molded fiberglass reinforced polyester composite pressure tested to ensure water will not wick or leak through. Finish in Bronze or Natural Brass. Bronze finish trim ring is a textured composite material. Clear convex, tempered soda-lime glass for high impact resistance. 2200 pound live-load rated, standard walk-over lens. 7 watt lamp with 24 or 36 degree beam spread included. Bronze finish includes Warm White 2700K LED module. Natural Brass finish includes Cool White 4000K color temperature. 30,000 hour lamp life. Lamps have 15 degree articulation either side of vertical and 358 degree rotation without interruption of beam pattern. Pre-wired with 3 foot pigtail of 18-2 AWG wire. Includes low voltage quick connector LVC3 for easy hook up to the low voltage supply cable not included. 6.6 inch diameter x 8.4 inch height. ETL listed for wet locations. Required remote transformer, optional mounting and optical accessories sold separately.





SHADE COLOR	Clear
BODY FINISH	Bronze
WATTAGE	7W
DIMMER	Dimmable
DIMENSIONS	6.6"W x 8.4"H
INTEGRATED LED MODULE	
LAMP	1 x LED/7W/12V LED

Technical Information

LAMP COLOR	2700K
BEAM ANGLE	24°

SPEC #	HAD119545
--------	-----------



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE