

IUL516 Composite LED Inground Uplight

SPEC # HAD119567



BRAND


Hadco by Signify

DESCRIPTION

IUL516 Composite LED Inground Uplight housing is fabricated from one piece injection molded high performance polymer composite. Bronze trim ring is a textured composite, pressure formed, molded in color. Lens ring is a single piece injection molded high performance polymer with gasketed lens and twist off operation for ease of maintenance. Clear convex, tempered glass furnished with silicone O-ring for watertight seal. 4 watt LED lamp included with 24 degree beam spread. 2700K Warm White color temperature. 30,000 hour lamp life. Also available in a low voltage halogen version. Pre-wired with 3 foot pigtail of 18-2 AWG wire. Includes low voltage quick connector LVC3 for easy hook up to the low voltage supply cable not included. 4.1 inch diameter x 4.3 inches high. Requires remote transformer not included.



SHADE COLOR Clear **BODY FINISH** Bronze WATTAGE /\\/ DIMMER Dimmable DIMENSIONS 4.1"W x 4.3"H INTEGRATED LED MODULE LAMP 1 x LED/4W/12V LED Technical Information LAMP COLOR 2700K



SPEC # HAD119567

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE