



**BRAND**

PureEdge Lighting

**DESCRIPTION**

Surface Mount Dry Location Light Channel features 24 volt Soft Strip inside a slim, paintable aluminum extrusion. LCSMC includes 2.5 watts per foot commercial grade LED Soft Strip with SS2C with (VW) 2700K color temperature in a 58 inch length. 50,000 hour average lamp life. The 61 degree white diffuser lens projects a clean line of light and eliminates LED dots. Fixtures include LC-MCL mounting clips every 2 feet and can be linked end-to-end with plug-in or flexible connectors to a maximum of 40 feet. System is powered by a dimmable electronic low voltage or 0-10V remote power supply. ELV power supplies include a 60, 100, 2X100, 3X100 or 4X100 watt option, dimmable with Legrand Adorne ADTP703TU, Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, or Lutron Radio Ra 2. 0-10V power supplies include a 96, 2X96, 3X96 or 4X96 watt option, dimmable with Philips Sunrise SR1200ZTUNV. Included Components: LC-CFX Flexible Connectors, SS-CFXT Flexible T-Connector, 3RE-WH Canopy Cover and Splice Box, and LC-MCL Mounting Clips. ETL listed. Major components made and assembled in the USA. 5 year warranty. Required power supply, dimmer control, and optional accessories sold separately. Product is built to order. Limited quantities available.



<b>SHADE COLOR</b>	Diffused Lens
<b>BODY FINISH</b>	Satin Aluminum
<b>WATTAGE</b>	0.6W
<b>DIMMER</b>	Dimmable
<b>DIMENSIONS</b>	3"L x 0.8"W x 0.68"H
<b>INTEGRATED LED MODULE</b>	
<b>LAMP</b>	1 x LED/0.62W/24V LED

*Technical Information*

<b>LUMINOUS FLUX</b>	43 lumens
<b>LUMENS/WATT</b>	69.35
<b>LAMP COLOR</b>	3000K
<b>COLOR RENDERING</b>	95 CRI

**SPEC #** EDG121956



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE