



BRAND PureEdge Lighting

DESCRIPTION

Millwork Light Channel features 24 volt Soft Strip inside a slim, paintable aluminum extrusion that recesses into wood (minimum .75 inch thick). LCMW includes 2.3 watts per foot of SS2P Soft Strip with 3000K Warm White, 80+ CRI LEDs for excellent color rendering. 37 lumens per watt/115 lumens per foot. 50,000 hour average lamp life. Finish available in Satin Aluminum. The white diffuser lens projects a clean line of light and eliminates LED dots. Fixtures include end caps, four LCMW-SC spring clips per foot, and can be linked with plug-in flexible connectors for a maximum of 40 feet. System is powered by a dimmable electronic low voltage or 0-10V remote power supply. ELV power supplies include a 60, 100, 2X100, 3X100 or 4X100 watt option, dimmable with Legrand Adorne ADTP703TU, Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, or Lutron Radio Ra 2. 0-10V power supplies include a 96, 2X96, 3X96 or 4X96 watt option, dimmable with Philips Sunrise SR1200ZTUNV. ETL listed. Major components made and assembled in the USA. 5 year warranty. Required power supply, dimmer control and optional accessories sold separately. Limited to quantities on hand.




SHADE COLOR	Diffused Lens
BODY FINISH	Satin Aluminum
WATTAGE	1W
DIMMER	Dimmable
DIMENSIONS	5.08"L x 1.25"W x 0.7"H
INTEGRATED LED MODULE	
LAMP	1 x LED/1W/24V LED

Technical Information

LUMINOUS FLUX	37 lumens
LUMENS/WATT	37.00
LAMP COLOR	3000K
COLOR RENDERING	80 CRI

SPEC # EDG123562



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE