

Light Channel Surface 2.6W RGB Wet

SPEC #

EDG125893

| D | E | s | IG | i N | E | R |
|---|---|---|----|-----|---|---|
| в | R | A | N | D | | |

Gregory Kay PureEdge Lighting

DESCRIPTION

Surface Mount Wet Location Light Channel features 24 volt RGB Soft Strip inside a slim paintable aluminum extrusion. RGB Soft Strip provides dynamic color effects with red, blue and green LEDs. System is sold in 4 inch increments up to 120 inches. 18 RGB LEDs per foot consuming 2.6 watts per foot. Average lamp life 32,000 hours. Provided with standard LC-MCL mounting clips with every two feet of Light Channel. Fixtures can be linked end-to-end with plug-in or flexible connectors to a maximum length of 36 feet before refeeding the power. Includes 8 foot power feed cable. The system can be powered using a compatible RGB 24 volt power supply with integrated RGB DMX driver. May be controlled using a Controller Dial (CDP) or Touch Screen (CTP), sold separately. Fixtures include a 5 year warranty. ETL listed. IP64 rated for covered areas in wet locations. Available in both a dry and wet location version. Major components made and assembled in the USA. Required power supply and controller sold separately. Product is built to order.

| | SHADE COLOR | | N/A | |
|---|-----------------------|---------|----------------------|--------|
| | BODY FINISH | | Satin Aluminum | |
| | WATTAGE | | 0.9W | |
| | DIMMER | | N/A | |
| | DIMENSIONS | | 4"L x 0.8"W x 0.68"H | |
| | INTEGRATED LED MODULE | | | |
| | LAMP | | LED/0.87W/24V LED | |
| | | | | |
| | Technical Information | | | |
| | COLOR RENDERING | | 80 CRI | |
| | | | | |
| | | | | |
| | | | | 0.7 |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | SPEC # | | EDG125893 | |
| | | | | |
| | | | | |
| | | | | |
| С | OMPANY | PROJECT | FIXTUR | E TYPE |



