



BRAND

ConTech

DESCRIPTION

50W Low Voltage Downlight Standard Housing. For use in any type of ceiling application. Lamp housing is removable through ceiling aperture for access to junction box. Sure-grip springs permit housing to be lowered and precisely adjust to ceiling thicknesses from 1/2 inch to 1 inch. In insulated ceilings, maintain a minimum 3 inch clearance around housing. 12V 50W MR16 50W max, GU5.3 base. Porcelain socket assembly with Molex connector. Magnetic Class H transformer with Molex disconnect in J-box is fully dimmable with magnetic low voltage dimmers. Transformer has internal thermal protection. 120V Transformer Ratings: Input: 120VAC, 60Hz, .54A, 65VA. Output: 12VAC, 60Hz, 4.2A, 50W. cULus listed. Suitable for damp locations.



TRIM COLOR	N/A
BODY FINISH	Galvanized Steel
WATTAGE	50W
DIMMER	Low Voltage Magnetic
DIMENSIONS	10.5"L x 5.75"W x 5.5"H
BULB NOT INCLUDED	
LAMP	1 x MR16/GU5.3 (bipin)/50W/12V Halogen 1 x MR16/GU5.3 (bipin)/12V LED

Technical Information

CEILING TYPE	Drywall with Trim
HOUSING TYPE	Remodel NON IC
HOUSING HEIGHT	6"

SPEC #	CNT24429
---------------	----------

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE