



BRAND PureEdge Lighting

DESCRIPTION

Soft Strip SS3 provides high levels of light with Very Warm White 2700K or Warm White 3000K color temperature LEDs, 75+ CRI, 93 lumens per watt/233 lumens per foot. 32,000 hour average lamp life. The .50 inch wide flexible copper strip with optically clear protective coating is sold in 1 foot increments up to 40 feet. Includes plug in connectors on each end and 6 foot power feed cable. For custom lengths, smaller segments are available in 4 inch increments, sold separately. Use plug in flexible connectors for making turns and custom configurations. Self adhering SS3 mounts to most smooth finished surfaces with industrial strength 3M tape provided on back of strip. Some unfinished surfaces may require screw in mounting clips, sold separately. Includes flexible aluminum heat sink to extend LED life. System can be powered using an electronic low voltage or 0-10V power supply. Electronic low voltage power supplies include a 24 volt 60 watt, 100 watt, 2X100 watt, 3X100 or 4X100 watt option, dimmable with a standard low voltage electronic dimmer (recommended Legrand Adorne ADTP703TU, Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, or Lutron Radio Ra). 0-10V power supplies include a 24 volt 96 watt, 2X96 watt, 3X96 watt or 4X96 watt option, dimmable with a 0-10 volt dimmer (recommended Philips Lightolier Sunrise SR1200ZTUNV). Designed for indoor/outdoor damp locations. ETL listed. Fixture includes a 5 year warranty. Required power supply, dimmer control and optional mounting accessories sold separately.



SHADE COLOR	N/A
BODY FINISH	Clear
WATTAGE	2.4W
DIMMER	Dimmable
DIMENSIONS	12"L x 0.5"W
INTEGRATED LED MODULE	
LAMP	1 x LED/2.4W/24V LED
Technical Information	
LAMP COLOR	3070K
COLOR RENDERING	75 CRI
SPEC #	EDG53814

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE