

# Lightology

lightology.com  
866-954-4489  
07-07-26

Project: \_\_\_\_\_

Company: \_\_\_\_\_

Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_

SPEC #: **EDG69737**

Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Soft Line LED 24V Double Row Indirect By PureEdge Lighting



### Description

Soft Line Indirect LED Lighting System provides soft, ambient, indirect illumination for decorative and architectural applications. For compact shipment and storage, Soft Line coils like a retractable tape measure. When uncoiled, the Soft Line becomes a 1.25 inch wide cupped, rigid aluminum channel that can be mounted on any angle between opposing wall, ceiling or floor surfaces. Soft Line is field-cuttable. Soft Line features a double row of 24 volt Soft Strip in 2700K, 3000K, 3500K, 4000K or 5700K color temperature. Includes Soft Line channel, a pair of power feed and non-power feed turnbuckles and a double row of LED Soft Strip. Soft Line 24 inch standoff, sold separately. Turnbuckles support Soft Line on any angle from 0-60 degrees, feed power from one end and mount to a standard 4 inch square electrical box with round plaster ring. Turnbuckles may be reversed and mounted (opposite the power feed) to a ceiling, wall or floor. Lengths over 20 feet require power feed at both ends. System is powered by a remote Universal (UNI) or Lutron Hi-Lume power supply sold separately. ETL listed. Title 24 compliant when used with a Universal (UNI) power supply. Power supply, standoff, and dimmer sold separately.



### Specifications

COLOR	N/A
BODY FINISH	Satin Aluminum
WATTAGE	50W
DIMMER	Dimmable
DIMENSIONS	120"L x 1.25"W
INTEGRATED LED MODULE	1x LED/50W/24V LED

### Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	3000K
LUMENS/WATT	115.60
LUMINOUS FLUX	5780 lumens

Notes: