



BRAND

PureEdge Lighting

DESCRIPTION

The Cirrus Power D1 Lens Linear Downlight Suspension with End Feed and One Canopy is a linear LED fixture that offers direct light in a clean, contemporary style. Available in a range of increments from 36 to 420 inches and features a 100 degree beam white diffused or 60 degree clear frosted (direct downlight lens). optional white or black louver, multiple finishes, three wattage options, and a spectrum of color temperature options. 60 degree lens not available without louver. Chrome finish available up to 84 inch length. Includes canopy with 120V/24VDC Class 2 electronic low voltage LED power supply and 12 foot adjustable coaxial cables. Additional aircraft cables provided for support when fixture exceeds 96 inches. Lengths over 96 inches ship in two segments. Canopy size (4, 5 or 6 inch) and power supply wattage dependent on length of fixture. For Non-IC the 50 watt (PS-60L-ELV) power supply will fit inside the electrical junction box with a flush 4.6 inch canopy. Optional accessories sold separately. Note: Product is built to order.



Shown in: Satin Nickel / White Lens


SHADE COLOR	White Lens
BODY FINISH	Satin Nickel
WATTAGE	21W
DIMMER	Low Voltage Electronic
DIMENSIONS	36"L x 0.9"W x 0.9"H
INTEGRATED LED MODULE	
LAMP	3 x LED/24V LED

Technical Information

LUMINOUS FLUX	723 lumens
LUMENS/WATT	103.29
LAMP COLOR	2700K
COLOR RENDERING	92 CRI

SPEC #

EDG99733



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE