

LOW-VOLTAGE PENDANTS

Peyton Pendant

DESCRIPTION


Cylindrical shade composed of glass mosaic tiles and inner frost glass diffuser. Includes low-voltage, 50 watt halogen bi-pin lamp or 8 watt replaceable 500 lumen 80 CRI 3000K LED SORAA® module and six feet of field-cutttable suspension cable.

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

WEIGHT

2.50lb / 1.13kg ±



brown



brown



white

ORDERING INFORMATION

700	SYSTEM	PEY	COLOR	FINISH	LAMP
FJ	FREEJACK		N BROWN	Z ANTIQUE BRONZE	12 VOLT HALOGEN
MP	MONOPOINT		W WHITE	C CHROME	-LEDS830 12 VOLT LED 80 CRI 3000K
MO	MONORAIL			S SATIN NICKEL	-24 24 VOLT HALOGEN
MO2	TWO-CIRCUIT MONORAIL				

Note: MP includes 4" Round Flush Canopy. Note: MP includes 4 Round Flush Canopy.

When installing LED option on MO2 only magnetic transformers may be used.



TECH LIGHTING®
 7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500
Tech Lighting, L.L.C.

700	___	PEY	___	___	___
FIXTURE TYPE: _____					
JOB NAME: _____					
NOTES: _____					

